

VG2436wm-LED

24" (23.6" VIEWABLE) WIDESCREEN LED MONITOR

WITH HEIGHT ADJUST, SPEAKERS
AND ENERGY STAR® 5.0

Planet-friendly. Picture perfect.

The VG2436wm-LED is one of two new members of ViewSonic's new VG36-LED family. Its 24" (23.6" viewable) display with a native 1920x1080 resolution is big enough to replace dual-monitor setups. What makes it even more appealing is the LED backlight for up to 50% energy savings. Monitor is also fully ergonomic with 90° pivot, height adjust, swivel and tilt. The slim bezel design coupled with hidden stereo speakers make VG2436wm-LED a space saver. You can put it on your desk or mount on your wall or on any VESA compliant monitor stand. With ViewSonic's strongest pixel performance guarantee and 3-year limited warranty, you will have peace of mind in your investment.




AMAZING GAMES AND HD CONTENT

- > **Up to 50% energy saving with LED backlight**
Without compromising your viewing quality and has eco-friendly mercury free LED backlight.
- > **Multi-functional base design (360° swivel and height adjust)**
VESA compliant wall-mount interface and detachable base for ergonomic flexibility with pivot, 5.3 height, tilt and 360° swivel adjustments.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Multimedia enhanced**
Stereo speakers provide clear and rich sound.
- > **MEGA dynamic contrast ratio at 20,000,000:1**
For true-to-life picture depth and clarity in any room.
- > **Widescreen aspect ratio with 1920x1080 resolution**
The widescreen aspect ratio allows you to view Full HD content in its native format with no stretching or distortion.
- > **Wall mountable design**
100mm x 100mm VESA compliant



VG2436wm-LED

24" (23.6" VIEWABLE) WIDESCREEN LED MONITOR WITH
HEIGHT ADJUST, SPEAKERS AND ENERGY STAR® 5.0



LCD	Type	24" (23.6" viewable) Wide Color TFT Active Matrix LCD
	Display Area	20.5" horizontal x 11.5" vertical; 23.6" diagonal
	Optimum Resolution	1920x1080
	Contrast Ratio	1000:1 (typ); 20,000,000:1 (dynamic)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 30,000 hrs. (typ)
VIDEO INPUT	Brightness	300 cd/m² (typ)
	Panel Surface	Anti-glare, hard-coating (3H)
	Analog	RGB analog (75 ohms, 0.7/1.0 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
COMPATIBILITY	Frequency	F _H : 24~83kHz, F _V : 50~76Hz
	Sync	H/V separated (TTL), composite sync-on-green
	PC	VGA up to 1920x1080 non-interlaced
	Mac®*	Power Mac™ up to 1920x1080
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Digital	DVI-D
	Audio	3.5 mm audio in
AUDIO POWER	Power	3-pin plug (CEE22)
	Speakers	2x2W
	Voltage	AC 100~240V (universal), 50/60Hz
CONTROLS	Consumption	30W (typ)
	Basic	Power, 1, down, up, 2
ERGONOMICS	OSD	Auto Image Adjust, Contrast/Brightness, Input Select (D-SUB, DVI), Audio adjust (volume, mute), Color Adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Eco-mode), Setup Menu (Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off), Memory Recall
	Tilt	Down 5°, Up 20°
	Swivel	360°
	Height Adjust	0-135mm
OPERATING CONDITIONS	Pivot	0-90°
	Temperature	32~104° F (0~40° C)
DIMENSIONS (W x H x D)	Humidity	20~90% (non-condensing)
	Physical with stand	22.29" x 17.06" x 9.42" (566.25mm x 433.38mm x 239.2mm)
	Physical without stand	22.29" x 13.83" x 2.06" (566.25mm x 351.22mm x 52.4mm)
	Packaging	25.39" x 19.37" x 7.28" (645mm x 492mm x 185mm)
WEIGHT	Net with stand	11.9 lb. (5.4 kg)
	Net without stand	8.92 lb. (4.05 kg)
	Gross	18.04 lb. (8.2 kg)
WALL MOUNT		VESA® 100mm x 100mm
REGULATIONS		BSMI, CCC, PSB, C-Tick, KC, e-standby, CE, Ergo, Gost-R/Hygienic, Ukraine, SASO, UL/cUL, FCC-B, ICES-B, TUV-S/UL-AR S Mark, NOM, WEEE, RoHS
POWER MANAGEMENT		ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, power cable, VGA cable, DVI cable, audio cable, Quick Start Guide ViewSonic Wizard CD (User Guide and drivers)
WARRANTY		Three-year limited warranty on parts, labor and backlight.



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.



Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows is a trademark of Microsoft Corporation registered in the U.S. and other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved. [15136-00B-07/10] VG2436wm-LED

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com